

SOFTTEL

SRXG-100WD

FTTH CATV Passive Node

(45~1050MHz)



HANGZHOU SOFTTEL OPTIC CO., LTD

info@softel-optic.com +86 13588723749

www.softel-optic.com

1.0 PRODUCT DESCRIPTION

SRXG-100WD CATV converter is for digital television, fiber to the home. This machine adopts the high sensitivity optical receiving tube, without power supply, no power consumption. When the input optical power output level Pin=-1dBm, Vo=68dBuV, economic, flexible application integration, application of fiber to the home network.

It is Built-in CWDM, suitable for single-fiber triple wavelength system, CATV operating Wavelength 1550nm, pass wavelength 1270/1577nm and 1310/1490nm, can conveniently connect the ONU of EPON, GPON, XG -PON.

2.0 PRODUCT FEATURE

1. No Power required
2. Work bandwidth 45~1050MHz

3.0 TEST DATA

Test Requency: 366MHz						
Pin (dBm)	Output Leve(dBuV)		MER		Output Difference	MER Difference
	Max	Min	Max	Min		
0	65.1	63.2	35	33.6	1.9	1.4
-1	64.4	61.9	35.5	34.7	2.5	0.8
-2	63.1	60.7	36.3	35.4	2.4	0.9
-3	62.1	59.6	37.8	35.5	2.5	2.3
-4	60.7	58.5	39.2	35.2	2.2	4
-5	58.6	56.5	39.8	35.7	2.1	4.1
-6	57.2	55.2	39.8	35.7	2	4.1
-7	55.5	53.5	39.5	35.5	2	4
-8	53.4	51.5	39.2	34.7	1.9	4.5
-9	51.3	50	37.3	35.2	1.3	2.1
-10	49.8	48.3	35.9	34	1.5	1.9
-11	47.9	46.4	34.5	32.3	1.5	2.2
-12	45.8	44.5	32.8	30.5	1.3	2.3
-13	43.9	42.4	31	28.7	1.5	2.3
-14	41.9	40.6	29.4	26.8	1.3	2.6
-15	39.9	38.7	27.7	25.7	1.2	2

4.0 TECHNICAL INDEX

	Optic feature	Unit	Index	Supplement
Optic Feature	CATV Work wavelength	(nm)	1540~1560	
	Pass wavelength	(nm)	1270/1577,	
	Channel Isolation	(dB)	≥40	1550nm&1490nm
	Receiving power	(dBm)	+1~-15	
	Optical return loss	(dB)	≥55	
	Optical fiber connector		SC/APC	Input
RF Feature	Work bandwidth	(MHz)	45~1050MHz	
	Output level	(dBμV)	61.9 - 64.4	Digital TV (Pin= -1dBm)
	Return loss	(dB)	≥14	47~862MHz
	Output impedance	(Ω)	75	
	Output port number		1	
	RF tie-in		F-Female	
Digital TV Feature	OMI	(%)	4.3	
	MER	(dB)	34.7 - 35.5	Pin= -1dBm
			28.7 - 31	Pin= -13dBm
BER		<1.0E-9	Pin: +1~-15dBm	
General Feature	Work temp	(°C)	-20~+55	
	Storage temp	(°C)	-40~85	
	Work relative temp	(%)	5~95	

5.0 PRODUCT SERIES

Model	Input wavelength	CATV Operating	Data pass	Output Fiber	Input Fiber
SRXG-100WD	1270, 1577,	1540~1560nm	1270/1577nm	SC/UPC OR	SC/APC
	1310,1490, 1550nm		1310/1490nm	SC/APC	

6.0 NOTE

1. When using the RF connector, and the RF input interface must be tightened to STB. Otherwise the ground is bad and will cause high frequency segments Digital TV signals MER degradation.
2. Keep the optical connector clean, the bad link will cause too low RF output level.

HANGZHOU SOFTEL OPTIC CO., LTD

www.softel-optic.com

info@softel-optic.com

+86 13588723749